

## Cross-Browser-Friendly JavaScript Objects (1 of 6)

Object	Properties	Methods	Event Handlers
Anchor	name	<i>none</i>	<i>none</i>
anchors ( <i>array</i> )	length	<i>none</i>	<i>none</i>
Applet		applet's methods	
applets ( <i>array</i> )	length	<i>none</i>	<i>none</i>
Area	hash host hostname href pathname port protocol search target	<i>none</i>	onMouseout onMouseover
Array	length	concat() join() reverse() slice() sort() splice() toString()	<i>none</i>
Button	form name type value	blur() click() focus()	onClick onMouseDown onMouseup
Checkbox	checked defaultChecked form name type value	blur() click() focus()	onClick onMouseDown onMouseup
Date	<i>none</i>	getDate() getDay() getFullYear() getHours() getMilliseconds() getMinutes() getMonth() getSeconds() getTime() getTimezoneOffset() getYear() parse() toGMTString() toLocaleString() toString() valueOf()	<i>none</i>

## Cross-Browser-Friendly JavaScript Objects (2 of 6)

Object	Properties	Methods	Event Handlers
document	alinkColor	clear()	
	Anchor	close()	
	anchors	open()	
	Applet	write()	
	Applets	writeln()	
	Area		
	bgColor		
	cookie		
	domain		
	embeds		
	fgColor		
	Form		
	forms		
	Image		
	Images		
	lastModified		
	linkColor		
	Link		
	links		
	location		
	plugins		
	referrer		
	title		
URL			
vlinkColor			
fileUpload	form	blur()	onBlur
	name	focus()	onFocus
	type	select()	onSelect
	value		
Form	action	reset()	onReset
	Button	submit()	onSubmit
	Checkbox		
	elements		
	encoding		
	FileUpload		
	Hidden		
	length		
	method		
	name		
	Password		
	Radio		
	Reset		
	Select		
	Submit		
	target		
Text			
Textarea			
forms (array)	length	none	none
frames (array)	length	none	none

## Cross-Browser-Friendly JavaScript Objects (3 of 6)

Object	Properties	Methods	Event Handlers
Hidden	form name type value	<i>none</i>	<i>none</i>
History	length	back() forward() go()	<i>none</i>
history ( <i>array</i> )	length	<i>none</i>	<i>none</i>
Image	border complete height hspace lowsrc name src vspace width	<i>none</i>	onAbort onError onLoad onReset onSubmit
images ( <i>array</i> )	length	<i>none</i>	<i>none</i>
links ( <i>array</i> )	length	<i>none</i>	<i>none</i>
location	hash host hostname href pathname port protocol search	assign() reload() replace()	<i>none</i>
Math	E LN2 LN10 LOG2E LOG10E PI SQRT1_2 SQRT2	abs() acos() asin() atan() atan2() ceil() cos() exp() floor() log() max() min() pow() random() round() sin() sqrt() tan()	<i>none</i>

## Cross-Browser-Friendly JavaScript Objects (4 of 6)

Object	Properties	Methods	Event Handlers
MimeType	description enabledPlugin suffixes type	<i>none</i>	<i>none</i>
mimeTypes ( <i>array</i> )	length	<i>none</i>	<i>none</i>
navigator	appName appVersion MimeType mimeTypes Plugin plugins userAgent	javaEnabled() taintEnabled()	<i>none</i>
Number	MAX_VALUE MIN_VALUE NaN NEGATIVE_INFINITY POSITIVE_INFINITY	toString() valueOf()	<i>none</i>
Option	defaultSelected index selected text value	<i>none</i>	<i>none</i>
options ( <i>array</i> )	length	<i>none</i>	<i>none</i>
Password	defaultValue form name type value	blur() focus() select()	onBlur onChange onFocus onSelect
Plugin	description filename length name	refresh()	<i>none</i>
plugins ( <i>array</i> )	length	<i>none</i>	<i>none</i>
Radio	checked defaultChecked form name type value	blur() click() focus()	onClick onMouseDown onMouseup

## Cross-Browser-Friendly JavaScript Objects (5 of 6)

Object	Properties	Methods	Event Handlers
radio ( <i>array</i> )	length	<i>none</i>	<i>none</i>
RegExp	input lastMatch lastParen leftContext multiline rightContext \$1...\$9	<i>none</i>	<i>none</i>
regular expresssion	global ignoreCase lastIndex source	compile() exec() test()	<i>none</i>
Reset	form name type value	blur() click() focus()	onClick onMouseDown onMouseup
screen	availHeight availWidth colorDepth height pixelDepth width	<i>none</i>	<i>none</i>
Select	form length name Option options selectedIndex type	blur() focus()	onBlur onChange onFocus
String	length	anchor() big() blink() bold() charAt() charCodeAt() concat() fixed() fontcolor() fontsize() fromCharCode() indexOf() italics() lastIndexOf() link() match() replace() search() slice()	<i>none</i>

## Cross-Browser-Friendly JavaScript Objects (6 of 6)

Object	Properties	Methods	Event Handlers
String ( <i>cont'd</i> )		small() split() strike() substr() substring() sup() toLowerCase() toString() toUpperCase() valueOf()	
Submit	form name type value	blur() click() focus()	onClick onMousedown onMouseup
Text	defaultValue form name type value	blur() click() focus() select()	onBlur onChange onFocus onKeyDown onKeyPress onKeyUp onSelect
Textarea	defaultValue form name type value	blur() click() focus() select()	onBlur onChange onFocus onHelp onKeyDown onKeyPress onKeyUp onSelect
window	closed defaultStatus document frames history location name opener parent self status top	alert() blur() clearInterval() clearTimeout() close() confirm() focus() moveBy() moveTo() open() print() prompt() resizeBy() resizeTo() scroll() scrollBy() scrollTo() setInterval() setTimeout()	onBlur onError onFocus onLoad onResize onUnload