

## Delayed Evaluation

---

For each language construct, there are rules governing when subexpressions get evaluated. In ML, Scheme, and Java:

- function arguments are “eager” (*call-by-value*)
- conditional branches are not

We could define a language in which function arguments were not evaluated before call, but instead at each use of argument in body. (*call-by-name*)

- Sometimes faster:  $(\text{lambda } (x) 3)$
- Sometimes slower:  $(\text{lambda } (x) (+ x x))$
- Equivalent if function argument has no effects/non-termination

## CSE 341: Programming Languages

Spring 2005  
Lecture 19 — Delayed Evaluation & Streams

CSE 341 Spring 2005, Lecture 19

1

CSE 341 Spring 2005, Lecture 19

2

## Streams

---

- A stream is an “infinite” list — you can ask for the rest of it as many times as you like and you’ll never get null.
- The universe is finite, so a stream must really be an object that acts like an infinite list.
- The idea: use a function to describe what comes next.

## An Example

---

The Riemann zeta function:

$$\zeta(s) = \prod_{i \geq 1} \frac{1}{1 - p_i^{-s}}$$

where  $p_i$  is the  $i^{\text{th}}$  prime.

CSE 341 Spring 2005, Lecture 19

3

CSE 341 Spring 2005, Lecture 19

4