CSE and EE 461
Lecture 14

Summer Quarter 1998

Medium Access Control (MAC)

- If instead of a point-to-point channel we have a broadcast channel what do we do to achieve good communication.
- Important in local area networks (LAN) - Ethernet
- Used also for packet radio and cellular telephone networks

  Metropolitan area networks (MAN)



Some Basic Terminology

- Collision - Several frames sent at nearly the same time collide.
- Collision detection - Collisions can be detected and transmission halted.

- Continuous time - transmissions can happen at any time
- Slotted time - transmissions only happen in time slots.



- Carrier sense - the channel can be sensed to see if a transmission is in progress.

The First MAC Protocols - Aloha

- In the 1970's the University of Hawaii set up a radio network for it different campuses on different islands.
- Frames were sent out by the stations and collisions could be detected and packets resent if necessary.
- A simple analysis uses the Poisson arrival process. Let us assume that frame times are of unit length and they are generated by a Poisson process with an average rate of G frames per second.
- Poisson process: The probability that k frames are generated in an interval t seconds is

$$P(k,t) = \frac{(Gt)^k e^{-Gt}}{k!}$$



Aloha Analysis

- Suppose a frame F is generated at time t, then the probability that some frame collides with F is the probability that a frame is generated between time t-1 and t+1.



- The probability that there is no frame generated between time t-1 and t+1 is e^{-2G}. Thus, the expected rate of frames being generated which are not involved in collisions is Ge^{-2G}. That is, the throughput in frames per second is Ge^{-2G}.
- Slotted aloha does better - throughput is Ge^{-G}.

Carrier Sense (CSMA)

- In a local area network the channel can be sensed. A station should not send if it hears that the channel is busy. Assume a slotted channel.
- 1-persistent protocol.

  if channel free - transmit
  if collision, wait a random increment of time
  if channel busy - wait until free
- non-persistent protocol.

  if channel free - transmit
  if collision, wait a random increment of time
  if channel busy - wait a random increment of time
- p-persistent protocol.

  if channel free - transmit with probability p
  if transmission results in collision, wait a random increment of time
  if channel busy - wait until free

Various Scenarios

1-persistent

non-persistent

p-persistent

Relative Performance

- 1-persistent - Waiters pile up and all transmit at once. Works best under light loads.
- non-persistent - Waiters spead themselves out by getting back into the protocol at different times. Better under high loads.
- p-persistent - Poor in light loads and good in heavy loads if p chosen well.