

# Building Java Programs

Chapter 3  
Lecture 3-1: Parameters

**reading: 3.1**

## Redundant recipes

- Recipe for baking **20** cookies:
  - Mix the following ingredients in a bowl:
    - **4** cups flour
    - **1** cup butter
    - **1** cup sugar
    - **2** eggs
    - **40** oz. chocolate chips ...
  - Place on sheet and Bake for about **10** minutes.
- Recipe for baking **40** cookies:
  - Mix the following ingredients in a bowl:
    - **8** cups flour
    - **2** cups butter
    - **2** cups sugar
    - **4** eggs
    - **80** oz. chocolate chips ...
  - Place on sheet and Bake for about **10** minutes.

# Parameterized recipe

- Recipe for baking **20** cookies:
  - Mix the following ingredients in a bowl:
    - **4** cups flour
    - **1** cup sugar
    - **2** eggs
    - ...
- Recipe for baking **N** cookies:
  - Mix the following ingredients in a bowl:
    - **N/5** cups flour
    - **N/20** cups butter
    - **N/20** cups sugar
    - **N/10** eggs
    - **2N** oz. chocolate chips ...
  - Place on sheet and Bake for about 10 minutes.
- **parameter**: A value that distinguishes similar tasks.

# Redundant figures

- Consider the task of printing the following lines/boxes:

\*\*\*\*\*

\*\*\*\*\*

\*\*\*\*\*

\*\*\*\*\*

\*           \*

\*\*\*\*\*

\*\*\*\*\*

\*       \*

\*       \*

\*\*\*\*\*

# A redundant solution

```
public class Stars1 {
    public static void main(String[] args) {
        lineOf13();
        lineOf7();
        lineOf35();
        box10x3();
        box5x4();
    }

    public static void lineOf13() {
        for (int i = 1; i <= 13; i++) {
            System.out.print("*");
        }
        System.out.println();
    }

    public static void lineOf7() {
        for (int i = 1; i <= 7; i++) {
            System.out.print("*");
        }
        System.out.println();
    }


    public static void lineOf35() {
        for (int i = 1; i <= 35; i++) {
            System.out.print("*");
        }
        System.out.println();
    }
    ...
}
```

- This code is redundant.
- Would variables help?  
Would constants help?
- What is a better solution?
  - line - A method to draw a line of any number of stars.
  - box - A method to draw a box of any size.

5

# Parameterization

- **parameter:** A value passed to a method by its caller.
  - Instead of `lineOf7`, `lineOf13`, write `line` to draw any length.
    - When *declaring* the method, we will state that it requires a parameter for the number of stars.
    - When *calling* the method, we will specify how many stars to draw.



6

## Declaring a parameter

*Stating that a method requires a parameter in order to run*

```
public static void <name> (<type> <name>) {  
    <statement>(s);  
}
```

- Example:

```
public static void sayPassword(int code) {  
    System.out.println("The password is: " + code);  
}
```

- When `sayPassword` is called, the caller must specify the integer code to print.

7

## Passing a parameter

*Calling a method and specifying values for its parameters*

```
<name> (<expression>);
```

- Example:

```
public static void main(String[] args) {  
    sayPassword(42);  
    sayPassword(12345);  
}
```

Output:

```
The password is 42  
The password is 12345
```

8

## Parameters and loops

- A parameter can guide the number of repetitions of a loop.

```
public static void main(String[] args) {  
    chant(3);  
}  
  
public static void chant(int times) {  
    for (int i = 1; i <= times; i++) {  
        System.out.println("Just a salad...");  
    }  
}
```

### Output:


```
Just a salad...  
Just a salad...  
Just a salad...
```

9

## How parameters are passed

- When the method is called:
  - The value is stored into the parameter variable.
  - The method's code executes using that value.

```
public static void main(String[] args) {  
    chant(3);  
    chant(7);  
}  
  
public static void chant(int times) {  
    for (int i = 1; i <= times; i++) {  
        System.out.println("Just a salad...");  
    }  
}
```



10

## Common errors

- If a method accepts a parameter, it is illegal to call it without passing any value for that parameter.

```
chant(); // ERROR: parameter value required
```

- The value passed to a method must be of the correct type.

```
chant(3.7); // ERROR: must be of type int
```

- Exercise: Change the `Stars` program to use a parameterized method for drawing lines of stars.

11

## Stars solution

```
// Prints several lines of stars.
// Uses a parameterized method to remove redundancy.
public class Stars2 {
    public static void main(String[] args) {
        line(13);
        line(7);
        line(35);
    }

    // Prints the given number of stars plus a line break.
    public static void line(int count) {
        for (int i = 1; i <= count; i++) {
            System.out.print("*");
        }
        System.out.println();
    }
}
```

12

## Multiple parameters

- A method can accept multiple parameters. (separate by , )
  - When calling it, you must pass values for each parameter.

- Declaration:

```
public static void <name>(<type> <name>, ..., <type> <name>) {  
    <statement>(s);  
}
```

- Call:

```
<name>(<exp>, <exp>, ..., <exp>);
```

13

## Multiple parameters example

```
public static void main(String[] args) {  
    printNumber(4, 9);  
    printNumber(17, 6);  
    printNumber(8, 0);  
    printNumber(0, 8);  
}  
  
public static void printNumber(int number, int count) {  
    for (int i = 1; i <= count; i++) {  
        System.out.print(number);  
    }  
    System.out.println();  
}
```

Output:

```
4444444444  
1717171717  
00000000
```

- Modify the Stars program to draw boxes with parameters.

14

## Stars solution

```
// Prints several lines and boxes made of stars.
// Third version with multiple parameterized methods.
public class Stars3 {
    public static void main(String[] args) {
        line(13);
        line(7);
        line(35);
        System.out.println();
        box(10, 3);
        box(5, 4);
        box(20, 7);
    }
    // Prints the given number of stars plus a line break.
    public static void line(int count) {
        for (int i = 1; i <= count; i++) {
            System.out.print("*");
        }
        System.out.println();
    }
    ...
}
```

15

## Stars solution, cont'd.

```
...
// Prints a box of stars of the given size.
public static void box(int width, int height) {
    line(width);
    for (int line = 1; line <= height - 2; line++) {
        System.out.print("*");
        for (int space = 1; space <= width - 2; space++) {
            System.out.print(" ");
        }
        System.out.println("*");
    }
    line(width);
}
}
```

16



# Value semantics

- **value semantics:** When primitive variables (`int`, `double`) are passed as parameters, their values are copied.
  - Modifying the parameter will not affect the variable passed in.

```
public static void strange(int x) {  
    x = x + 1;  
    System.out.println("1. x = " + x);  
}  
  
public static void main(String[] args) {  
    int x = 23;  
    strange(x);  
    System.out.println("2. x = " + x);  
    ...  
}
```

Output:

```
1. x = 24  
2. x = 23
```

17

# A "Parameter Mystery" problem

```
public class ParameterMystery {  
    public static void main(String[] args) {  
        int x = 9;  
        int y = 2;  
        int z = 5;  
  
        mystery(z, y, x);  
  
        mystery(y, x, z);  
    }  
  
        
    public static void mystery(int x, int z, int y) {  
        System.out.println(z + " and " + (y - x));  
    }  
}
```

18

# Strings

- **string**: A sequence of text characters.

```
String <name> = "<text>";  
String <name> = <expression resulting in String>;
```

- Examples:

```
String name = "Marla Singer";  
int x = 3;  
int y = 5;  
String point = "(" + x + ", " + y + ")";
```

19

# Strings as parameters

```
public class StringParameters {  
    public static void main(String[] args) {  
        sayHello("Marty");  
        String teacher = "Bictolia";  
        sayHello(teacher);  
    }  
    public static void sayHello(String name) {  
        System.out.println("Welcome, " + name);  
    }  
}
```

## Output:

```
Welcome, Marty  
Welcome, Bictolia
```

- Modify the `Stars` program to use string parameters. Use a method named `repeat` that prints a string many times.

20

## Stars solution

```
// Prints several lines and boxes made of stars.
// Fourth version with String parameters.
public class Stars4 {
    public static void main(String[] args) {
        line(13);
        line(7);
        line(35);
        System.out.println();
        box(10, 3);
        box(5, 4);
        box(20, 7);
    }
    // Prints the given number of stars plus a line break.
    public static void line(int count) {
        repeat("*", count);
        System.out.println();
    }
    ...
}
```

21

## Stars solution, cont'd.

```
...
// Prints a box of stars of the given size.
public static void box(int width, int height) {
    line(width);
    for (int line = 1; line <= height - 2; line++) {
        System.out.print("*");
        repeat(" ", width - 2);
        System.out.println("*");
    }
    line(width);
}
// Prints the given String the given number of times.
public static void repeat(String s, int times) {
    for (int i = 1; i <= times; i++) {
        System.out.print(s);
    }
}
}
```

22