

CSE 142, Spring 2013

Chapter 5
Lecture 5-1: `while` Loops,
Fencepost Loops, and Sentinel Loops

reading: 5.1 – 5.2

```
while (mahself.stillAwake())  
{  
    sheep++;  
}
```



Methods using `charAt`

- Write a method `printConsonants` that accepts a `String` as a parameter and prints out that `String` with all vowels removed

For example, the call:

```
printConsonants("atmosphere")
```

should print:

```
tmsphr
```

A deceptive problem...

- Write a method `printLetters` that prints each letter from a word separated by commas.

For example, the call:

```
printLetters("Atmosphere")
```

should print:

```
A, t, m, o, s, p, h, e, r, e
```

Flawed solutions

- ```
public static void printLetters(String word) {
 for(int i = 0; i < word.length(); i++) {
 System.out.print(word.charAt(i) + ", ");
 }
 System.out.println(); // end line
}
```

- **Output:** A, t, m, o, s, p, h, e, r, e,


- ```
public static void printLetters(String word) {  
    for(int i = 0; i < word.length(); i++) {  
        System.out.print(", " + word.charAt(i));  
    }  
    System.out.println();    // end line  
}
```

- **Output:** , A, t, m, o, s, p, h, e, r, e

Fence post analogy

- We print n letters but need only $n - 1$ commas.
- Similar to building a fence with wires separated by posts:
 - If we use a flawed algorithm that repeatedly places a post + wire, the last post will have an extra dangling wire.

*for (length of fence) {
 place a post.
 place some wire.
}*



Fencepost loop

- Add a statement outside the loop to place the initial "post."
 - Also called a *fencepost loop* or a "loop-and-a-half" solution.


place a post.

for (length of fence - 1) {

place some wire.

place a post.

}



Fencepost method solution

- ```
public static void printLetters(String word) {
 System.out.print(word.charAt(0));
 for(int i = 1; i < word.length(); i++) {
 System.out.print(", " + word.charAt(i));
 }
 System.out.println(); // end line
}
```

- Alternate solution: Either first or last "post" can be taken out:

```
public static void printLetters(String word) {
 for(int i = 0; i < word.length() - 1; i++) {
 System.out.print(word.charAt(i) + ", ");
 }
 int last = word.length() - 1;
 System.out.println(word.charAt(last)); // end line
}
```



# Fencepost question

- Write a method `printPrimes` that prints all *prime* numbers up to a max.
  - Example: `printPrimes(50)` prints  
`2, 3, 5, 7, 11, 13, 17, 19, 23, 29, 31, 37, 41, 43, 47`
  - If the maximum is less than 2, print no output.
- To help you, write a method `countFactors` which returns the number of factors of a given integer.
  - `countFactors(20)` returns 6 due to factors 1, 2, 4, 5, 10, 20.

# Fencepost answer

```
// Prints all prime numbers up to the given max.
```

```
public static void printPrimes(int max) {
 if (max >= 2) {
 System.out.print("2");
 for (int i = 3; i <= max; i++) {
 if (countFactors(i) == 2) {
 System.out.print(", " + i);
 }
 }
 System.out.println();
 }
}
```

```
// Returns how many factors the given number has.
```

```
public static int countFactors(int number) {
 int count = 0;
 for (int i = 1; i <= number; i++) {
 if (number % i == 0) {
 count++; // i is a factor of number
 }
 }
 return count;
}
```

# while loops

**reading: 5.1**

# Categories of loops

- **definite loop:** Executes a known number of times.
  - The `for` loops we have seen are definite loops.
    - Print "hello" 10 times.
    - Find all the prime numbers up to an integer  $n$ .
    - Print each odd number between 5 and 127.
- **indefinite loop:** One where the number of times its body repeats is not known in advance.
  - Prompt the user until they type a non-negative number.
  - Print random numbers until a prime number is printed.
  - Repeat until the user has typed "q" to quit.

# The while loop

- **while loop:** Repeatedly executes its body as long as a logical test is true.

```
while (test) {
 statement(s);
}
```


- Example:

```
int num = 1;
while (num <= 200) {
 System.out.print(num + " ");
 num = num * 2;
}
```

```
// output: 1 2 4 8 16 32 64 128
```

```
// initialization
// test

// update
```



# Example while loop

```
// finds the first factor of 91, other than 1
int n = 91;
int factor = 2;
while (n % factor != 0) {
 factor++;
}
System.out.println("First factor is " + factor);
// output: First factor is 7
```

- `while` is better than `for` because we don't know how many times we will need to increment to find the factor.

# Sentinel values

- **sentinel**: A value that signals the end of user input.
  - **sentinel loop**: Repeats until a sentinel value is seen.
- Example: Write a program that prompts the user for text until the user types "quit", then output the total number of characters typed.
  - (In this case, "quit" is the sentinel value.)

```
Type a word (or "quit" to exit): hello
Type a word (or "quit" to exit): yay
Type a word (or "quit" to exit): quit
You typed a total of 8 characters.
```

# Solution?

```
Scanner console = new Scanner(System.in);
int sum = 0;
String response = "dummy"; // "dummy" value, anything but "quit"

while (!response.equals("quit")) {
 System.out.print("Type a word (or \"quit\" to exit): ");
 response = console.next();
 sum += response.length();
}

System.out.println("You typed a total of " + sum + " characters.");
```

- This solution produces the wrong output. Why?  
You typed a total of 12 characters.



# The problem with our code

- Our code uses a pattern like this:

```
sum = 0.
while (input is not the sentinel) {
 prompt for input; read input.
 add input length to the sum.
}
```

- On the last pass, the sentinel's length (4) is added to the sum:

```
prompt for input; read input ("quit").
add input length (4) to the sum.
```

- This is a fencepost problem.
  - Must read  $N$  lines, but only sum the lengths of the first  $N-1$ .

# A fencepost solution

```
sum = 0.
prompt for input; read input. // place a "post"

while (input is not the sentinel) {
 add input length to the sum. // place a "wire"
 prompt for input; read input. // place a "post"
}
```

- Sentinel loops often utilize a fencepost "loop-and-a-half" style solution by pulling some code out of the loop.

# Correct code

```
Scanner console = new Scanner(System.in);
int sum = 0;

// pull one prompt/read ("post") out of the loop
System.out.print("Type a word (or \"quit\" to exit): ");
String response = console.next();

while (!response.equals("quit")) {
 sum += response.length(); // moved to top of loop
 System.out.print("Type a word (or \"quit\" to exit): ");
 response = console.next();
}

System.out.println("You typed a total of " + sum + " characters.");
```

# Sentinel as a constant

```
public static final String SENTINEL = "quit";
...

Scanner console = new Scanner(System.in);
int sum = 0;

// pull one prompt/read ("post") out of the loop
System.out.print("Type a word (or \" + SENTINEL + "\" to exit): ");
String response = console.next();

while (!response.equals(SENTINEL)) {
 sum += response.length(); // moved to top of loop
 System.out.print("Type a word (or \" + SENTINEL + "\" to exit): ");
 response = console.next();
}

System.out.println("You typed a total of " + sum + " characters.");
```