
CSE 143

Stacks and Queues

Reading: Secs. 25.1 & 25.2

12/2/2004

(c) 2001-4, University of Washington

17-1

Typing and Correcting Chars

- What data structure would you use for this problem?
 - User types characters on the command line
 - Until she hits enter, the backspace key (<) can be used to "erase the previous character"

12/2/2004

(c) 2001-4, University of Washington

17-2

Sample

- | • <u>Action</u> | • <u>Result</u> |
|-----------------|-----------------|
| • type h | • h |
| • type e | • he |
| • type l | • hel |
| • type o | • helo |
| • type < | • hel |
| • type l | • hell |
| • type w | • hellw |
| • type < | • hell |
| • type < | • hel |
| • type < | • he |
| • type < | • h |
| • type i | • hi |

12/2/2004

(c) 2001-4, University of Washington

17-3

Analysis

- We need to store a sequence of characters
- The order of the characters in the sequence is significant
- Characters are added at the end of the sequence
- We only can remove the most recently entered character

- We need a data structure that is *Last in, first out*, or LIFO
 - a stack
 - Many examples in real life: stuff on top of your desk, trays in the cafeteria, discard pile in a card game, ...


12/2/2004

(c) 2001-4, University of Washington

17-4

Stack Terminology

- **Top:** Uppermost element of stack,
 - first to be removed
- **Bottom:** Lowest element of stack,
 - last to be removed
- Elements are always inserted and removed from the top (LIFO – Last In, First Out)



12/2/2004

(c) 2001-4, University of Washington

17-5

Stack Operations

- **push(Object):** Add an element to the top of the stack, increasing stack height by one
- **Object pop():** Remove topmost element from stack and return it, decreasing stack height by one
- **Object top():** Returns a copy of topmost element of stack, leaving stack unchanged
- **No "direct access"**
 - cannot index to a particular data item
- **No convenient way to traverse the collection**


12/2/2004

(c) 2001-4, University of Washington

17-6

Picturing a Stack

- Stack pictures are usually somewhat abstract
- Not necessary to show details of object references, names, etc.
 - Unless asked to do so, or course!
- "Top" of stack can be up, down, left, right – just label it.




12/2/2004

(c) 2001-4, University of Washington

17-7

What is the result of...

```
Stack s;
Object v1,v2,v3,v4,v5,v6;
s.push("Yawn");
s.push("Burp");
v1 = s.pop();
s.push("Wave");
s.push("Hop");
v2 = s.pop();
s.push("Jump");
v3 = s.pop();
v4 = s.pop();
v5 = s.pop();
v6 = s.pop();
```



v1 v2 v3 v4 v5 v6

12/2/2004

(c) 2001-4, University of Washington

17-8

Stack Practice

- Show the changes to the stack in the following example:

```
Stack s;  
Object obj;  
s.push("abc");  
s.push("xyzy");  
s.push("secret");  
obj = s.pop();  
obj = s.top();  
s.push("swordfish");  
s.push("terces");
```

12/2/2004

(c) 2001-4, University of Washington

17-9

Stack Implementations

- Several possible ways to implement
 - An array
 - A linked listHow would you do these? Tradeoffs?
- Java library does not have a Stack class
- Easiest way in Java: implement with some sort of List
 - `push(Object)` `add(Object)`
 - `top()` `get(size() -1)`
 - `pop()` `remove(size() -1)`
- Precondition for `top()` and `pop()`: stack not empty
- Cost of operations? $O(?)$

12/2/2004

(c) 2001-4, University of Washington

17-10

An Application: What Model Do We Want?

- waiting line at the movie theater...
- job flow on an assembly line...
- traffic flow at the airport....
- "Your call is important to us. Please stay on the line. Your call will be answered in the order received. Your call is important to us..."
- ...
- Characteristics
 - Objects enter the line at one end (rear)
 - Objects leave the line at the other end (front)
- This is a "*first in, first out*" (FIFO) data structure.




12/2/2004

(c) 2001-4, University of Washington

17-11

Queue Definition

- Queue: Ordered collection, accessed only at the front (remove) and rear (insert)
 - Front: First element in queue
 - Rear: Last element of queue
- FIFO: First In, First Out
- Footnote: picture can be drawn in any direction



12/2/2004

(c) 2001-4, University of Washington

17-12

Abstract Queue Operations

- **insert(Object)** – Add an element to rear of a queue
 - succeeds unless the queue is full (if implementation is bounded)
 - often called “**enqueue**”
- Object **front()** – Return a copy of the front element of a queue
 - precondition: queue is not empty
- Object **remove()** – Remove and return the front element of a queue
 - precondition: queue is not empty
 - often called “**dequeue**”

12/2/2004

(c) 2001-4, University of Washington

17-13

Queue Example

- Draw a picture and show the changes to the queue in the following example:

Queue q; Object v1, v2;

```
q.insert("chore");
q.insert("work");
q.insert("play");
v1 = q.remove();
v2 = q.front();
q.insert("job");
q.insert("fun");
```

12/2/2004

(c) 2001-4, University of Washington

17-14

What is the result of:

Queue q; Object v1,v2,v3,v4,v5,v6

```
q.insert("Sue");
q.insert("Sam");
q.insert("Sarah");
v1 = q.remove();
v2 = q.front();
q.insert("Seymour");
v3 = q.remove();
v4 = q.front();
q.insert("Sally");
v5 = q.remove();
v6 = q.front();
```

12/2/2004

(c) 2001-4, University of Washington

17-15

Queue Implementations

- Similar to stack
 - Array – trick here is what you do when you run off the end
 - Linked list – ideal, if you have both a *first* and a *last* pointer.
- No standard Queue class in Java library
- Easiest way in Java: use LinkedList class
 - **insert(Object)** addLast(Object) [or add(Object)]
 - **getFront()** getFirst()
 - **remove()** removeFirst()

Interesting "coincidence" – a Java LinkedList supports exactly the operations you would want to implement queues. Internally it uses a doubly-linked list, where each node has a reference to the previous node as well as the next one

12/2/2004

(c) 2001-4, University of Washington

17-16

Bounded vs Unbounded

- In the abstract, queues and stacks are generally thought of as "unbounded": no limit to the number of items that can be inserted.
- In most practical applications, only a finite size can be accommodated: "bounded".
- Assume "unbounded" unless you hear otherwise.
 - Makes analysis and problem solution easier
 - Well-behaved applications rarely reach the physical limit
- When the boundedness of a queue is an issue, it is sometimes called a "buffer"
 - People speak of bounded buffers and unbounded buffers
 - Frequent applications in systems programming
E.g. incoming packets, outgoing packets

12/2/2004

(c) 2001-4, University of Washington

17-17

Summary

- Stacks and Queues
 - Specialized list data structures for specific applications
- Stack
 - LIFO (Last in, first out)
 - Operations: push(Object), top(), and pop()
- Queue
 - FIFO (First in, first out)
 - Operations: insert(Object), getFront(), and remove()
- Implementations: arrays or lists are possibilities for each



12/2/2004

(c) 2001-4, University of Washington

17-18