

C++ Class Details, Heap

CSE 333 Winter 2019

Instructor: Hal Perkins

Teaching Assistants:

Alexey Beall

Renshu Gu

Harshita Neti

David Porter

Forrest Timour

Soumya Vasisht

Yifan Xu

Sujie Zhou

Administrivia

- ❖ Yet another exercise released today, due ~~Wed.~~ Mon.
 - Rework exercise 10 but with dynamic memory this time
 - Fine to use ex10 solution as a starting point for ex11
- ❖ Should be due before Fri. lecture, but can't because...
- ❖ ...Homework 2 due Thursday (tomorrow!) night
 - File system crawler, indexer, and search engine
- ❖ Not clear what to do about exercise based on Fri. lecture
 - 2nd exercise due Monday? (☹️ but maybe need to catch up?)

Lecture Outline

- ❖ **Class Details**
 - Filling in some gaps from last time
- ❖ Using the Heap
 - `new / delete / delete []`

Rule of Three

- ❖ If you define any of:
 - 1) Destructor
 - 2) Copy Constructor
 - 3) Assignment (`operator=`)
- ❖ Then you should normally define all three
 - Can explicitly ask for default synthesized versions (C++11):

```
class Point {  
public:  
    Point() = default; // the default ctor  
    ~Point() = default; // the default dtor  
    Point(const Point& copyme) = default; // the default cctor  
    Point& operator=(const Point& rhs) = default; // the default "="  
    ...  
};
```

Dealing with the Insanity

❖ C++ style guide tip:

- If possible, **disable** the copy constructor and assignment operator by declaring as private and not defining them (pre-C++11)

Point.h

```
class Point {
public:
    Point(const int x, const int y) : x_(x), y_(y) { } // ctor
    ...
private:
    Point(const Point& copyme); // disable cctor (no def.)
    Point& operator=(const Point& rhs); // disable "=" (no def.)
    ...
}; // class Point

Point w; // compiler error (no default constructor)
Point x(1, 2); // OK!
Point y = w; // compiler error (no copy constructor)
y = x; // compiler error (no assignment operator)
```

Disabling in C++11

- ❖ C++11 add new syntax to do this directly
 - This is the better choice in C++11 code

Point_2011.h

```
class Point {
public:
    Point(const int x, const int y) : x_(x), y_(y) { } // ctor
    ...
    Point(const Point& copyme) = delete; // declare ctor and "=" as
    Point& operator=(const Point& rhs) = delete; // as deleted (C++11)
private:
    ...
}; // class Point

Point w; // compiler error (no default constructor)
Point x(1, 2); // OK!
Point y = w; // compiler error (no copy constructor)
y = x; // compiler error (no assignment operator)
```

CopyFrom

❖ C++11 style guide tip:

- If you disable them, then you instead may want an explicit “CopyFrom” function that can be used when occasionally needed

Point.h

```
class Point {
public:
    Point(const int x, const int y) : x_(x), y_(y) { } // ctor
    void CopyFrom(const Point& copy_from_me);
    ...
    Point(Point& copyme) = delete; // disable ctor
    Point& operator=(Point& rhs) = delete; // disable "="
private:
    ...
}; // class Point
```

sanepoint.cc

```
Point x(1, 2); // OK
Point y(3, 4); // OK
x.CopyFrom(y); // OK
```

struct vs. class

- ❖ In C, a `struct` can only contain data fields
 - Has no methods and all fields are always accessible
- ❖ In C++, `struct` and `class` are (nearly) the same!
 - Both can have methods and member visibility (public/private/protected)
 - Only real (minor) difference: members are default *public* in a `struct` and default *private* in a `class`
- ❖ Common style/usage convention:
 - Use `struct` for simple bundles of data
 - Use `class` for abstractions with data + functions

Access Control

❖ Access modifiers for members:

- `public`: accessible to *all* parts of the program
- `private`: accessible to the member functions of the class
 - Private to *class*, not object instances
- `protected`: accessible to member functions of the class and any *derived* classes (subclasses – more to come, later)

❖ Reminders:

- Access modifiers apply to *all* members that follow until another access modifier is reached
- If no access modifier is specified, `struct` members default to `public` and `class` members default to `private`

Nonmember Functions

- ❖ “Nonmember functions” are just normal functions that happen to use some class
 - Called like a regular function instead of as a member of a class object instance
 - This gets a little weird when we talk about operators...
 - These do *not* have access to the class’ private members
- ❖ Useful nonmember functions often included as part of interface to a class
 - Declaration goes in header file, but *outside* of class definition

friend Nonmember Functions

- ❖ A class can give a nonmember function (or class) access to its `nonpublic` members by declaring it as a `friend` within its definition
 - `friend` function is not a class member, but has access privileges as if it were
 - `friend` functions are usually unnecessary if your class includes appropriate “getter” public functions

Complex.h

```
class Complex {  
    ...  
    friend std::istream& operator>>(std::istream& in, Complex& a);  
    ...  
}; // class Complex
```

```
std::istream& operator>>(std::istream& in, Complex& a) {  
    ...  
}
```

Complex.cc 11

Namespaces

- ❖ Each namespace is a separate scope
 - Useful for avoiding symbol collisions!

- ❖ Namespace definition:

- ```
namespace name {
 // declarations go here
}
```

- Creates a new namespace name if it did not exist, otherwise *adds to the existing namespace (!)*
  - This means that components (classes, functions, etc.) of a namespace can be defined in multiple source files

# Classes vs. Namespaces

- ❖ They seems somewhat similar, but classes are *not* namespaces:
  - There are no instances/objects of a namespace; a namespace is just a group of logically-related things (classes, functions, etc.)
  - To access a member of a namespace, you must use the fully qualified name (*i.e.* `nsp_name::member`)
    - Unless you are `using` that namespace
    - You only used the fully qualified name of a class member when you are defining it outside of the scope of the class definition

# Lecture Outline

- ❖ Class Details
  - Filling in some gaps from last time
- ❖ **Using the Heap**
  - `new / delete / delete []`

# C++11 `nullptr`

- ❖ C and C++ have long used `NULL` as a pointer value that references nothing
- ❖ C++11 introduced a new literal for this: `nullptr`
  - New reserved word
  - Interchangeable with `NULL` for all practical purposes, but it has type  $T^*$  for any/every  $T$ , and is not an integer value
    - Avoids funny edge cases (see C++ references for details)
    - Still can convert to/from integer `0` for tests, assignment, etc.
  - Advice: prefer `nullptr` in C++11 code
    - Though `NULL` will also be around for a long, long time

# new/delete

- ❖ To allocate on the heap using C++, you use the `new` keyword instead of `malloc()` from `stdlib.h`
  - You can use `new` to allocate an object (*e.g.* `new Point`)
  - You can use `new` to allocate a primitive type (*e.g.* `new int`)
- ❖ To deallocate a heap-allocated object or primitive, use the `delete` keyword instead of `free()` from `stdlib.h`
  - Don't mix and match!
    - Never `free()` something allocated with `new`
    - Never `delete` something allocated with `malloc()`
    - Careful if you're using a legacy C code library or module in C++



# new/delete Example

```
int* AllocateInt(int x) {
 int* heapy_int = new int;
 *heapy_int = x;
 return heapy_int;
}
```

```
Point* AllocatePoint(int x, int y) {
 Point* heapy_pt = new Point(x, y);
 return heapy_pt;
}
```

heappoint.cc

```
#include "Point.h"
using namespace std;

... // definitions of AllocateInt() and AllocatePoint()

int main() {
 Point* x = AllocatePoint(1, 2);
 int* y = AllocateInt(3);

 cout << "x's x_coord: " << x->get_x() << endl;
 cout << "y: " << y << ", *y: " << *y << endl;

 delete x;
 delete y;
 return 0;
}
```

# Dynamically Allocated Arrays

## ❖ To dynamically allocate an array:

- Default initialize: `type* name = new type[size];`

## ❖ To dynamically deallocate an array:

- Use `delete[] name;`

- It is an *incorrect* to use “`delete name;`” on an array
  - The compiler probably won't catch this, though (!) because it can't always tell if `name*` was allocated with `new type[size];` or `new type;`
    - Especially inside a function where a pointer parameter could point to a single item or an array and there's no way to tell which!
  - Result of wrong `delete` is undefined behavior

# Arrays Example (primitive)

arrays.cc

```
#include "Point.h"
using namespace std;

int main() {
 int stack_int;
 int* heap_int = new int;
 int* heap_init_int = new int(12);

 int stack_arr[10];
 int* heap_arr = new int[10];

 int* heap_init_arr = new int[10](); // uncommon usage
 int* heap_init_error = new int[10](12); // bad syntax

 ...

 delete heap_int; //
 delete heap_init_int; //
 delete heap_arr; //
 delete[] heap_init_arr; //

 return 0;
}
```

# Arrays Example (class objects)

arrays.cc

```
#include "Point.h"
using namespace std;

int main() {
 ...

 Point stack_point(1, 2);
 Point* heap_point = new Point(1, 2);

 Point* err_pt_arr = new Point[10]; // no Point() ctor
 Point* err2_pt_arr = new Point[10](1,2); // bad syntax
 ...

 delete heap_point;

 ...

 return 0;
}
```

# malloc vs. new

|                          | <code>malloc()</code>                           | <code>new</code>                                         |
|--------------------------|-------------------------------------------------|----------------------------------------------------------|
| What is it?              | a function                                      | an operator or keyword                                   |
| How often used (in C)?   | often                                           | never                                                    |
| How often used (in C++)? | rarely                                          | often                                                    |
| Allocated memory for     | anything                                        | arrays, structs, objects, primitives                     |
| Returns                  | a <code>void*</code><br><i>(should be cast)</i> | appropriate pointer type<br><i>(doesn't need a cast)</i> |
| When out of memory       | returns <code>NULL</code>                       | throws an exception                                      |
| Deallocating             | <code>free()</code>                             | <code>delete</code> or <code>delete []</code>            |

# Heap Member Example

- ❖ Let's build a class to simulate some of the functionality of the C++ string
  - Internal representation: c-string to hold characters
- ❖ What might we want to implement in the class?

# Str Class Walkthrough

Str.h

```
#include <iostream>
using namespace std;

class Str {
public:
 Str(); // default ctor
 Str(const char* s); // c-string ctor
 Str(const Str& s); // copy ctor
 ~Str(); // dtor

 int length() const; // return length of string
 char* c_str() const; // return a copy of st_
 void append(const Str& s);

 Str& operator=(const Str& s); // string assignment

 friend std::ostream& operator<<(std::ostream& out, const Str& s);

private:
 char* st_; // c-string on heap (terminated by '\0')
}; // class Str
```

# Str Example Walkthrough

See:

`Str.h`

`Str.cc`

`strtest.cc`

- ❖ Look carefully at assignment `operator=`
  - self-assignment test is especially important here



# Extra Exercise #1

- ❖ Write a C++ function that:
  - Uses `new` to dynamically allocate an array of strings and uses `delete []` to free it
  - Uses `new` to dynamically allocate an array of pointers to strings
    - Assign each entry of the array to a string allocated using `new`
  - Cleans up before exiting
    - Use `delete` to delete each allocated string
    - Uses `delete []` to delete the string pointer array
    - (whew!)