CSE 451: Operating Systems

Section 8
Linux buffer cache; design principles

Outline

- ★Thread preemption (project 2b)
- *RPC
- *Linux buffer cache
- **★**Networking design principles

12/2/10

Mutex: no preemption

```
mutex lock(lock)
                        mutex unlock(lock)
  if (lock->held == 0)     if (!is empty(
                        lock->waitq))
    lock->held = 1;
                          next = dequeue(
  else
    enqueue (
                            lock->waitq);
      lock->waitq,
                            enqueue (readyq,
      current);
                              next);
    schedule();
                        else
                            lock->held = 0;
12/2/10
```

Mutex: with preemption (wrong)

2/2/10 4

Mutex: with preemption (wrong)

Mutex: with preemption (wrong)

```
mutex lock(lock)
                          mutex unlock(lock)
  while(test and set
                            if (!is empty(
    (lock->held))
                               lock->waitq))
    enqueue (
                               splx(HIGH);
      lock->waitq,
                               next = dequeue(
      current);
                                 lock->waitq);
    schedule();
                               enqueue (readyq,
                                 next);
                               splx(LOW);
                             atomic clear (
                               lock->held);
12/2/10
                                                  6
```

Mutex: with preemption (wrong)

```
mutex lock(lock)
                           mutex unlock(lock)
  while(test and set
                             if (!is_empty(
     (lock->held))
                               lock->waitq))
                     What if -
    enqueue (
                               splx(HIGH);
                     prempted
                     here?
      lock->waitq,
                               next = dequeue(
      current);
                                 lock->waitq);
    schedule();
                               enqueue (readyq,
                                 next);
                               splx(LOW);
                             atomic_clear(
                               lock->held);
12/2/10
```

Mutex: with preemption (right)

```
mutex lock(lock)
                             mutex unlock(lock)
 while(test and set(
                                while (test and set (
   lock->codelock))
                                  lock->codelock))
 if (lock->held == 0)
                                if (!is empty(
   lock->held = 1;
                                  lock->waitq))
   atomic clear(
                                  next = dequeue(
     lock->codelock)
                                   lock->waitq);
                                  splx(HIGH);
   enqueue (
                                  enqueue (readyq,
     lock->waitq,
                                    next);
                                  splx(LOW);
     current);
   atomic clear (
     lock->codelock)
                                  lock->held = 0;
   schedule();
                                atomic clear(
                                  lock->codelock)
```

RPC

12/2/10

RPC


- *Remote procedure call: causes a procedure to execute in some other address space
 - * Usually an address space on some other machine
- *Interface description language (IDL) defines the interface that the server makes available to the client

12/2/10

RPC on Android

- *Android uses RPC for communication between applications and system components
 - * All on the same device!
- **★**Uses all of the standard RPC components:
 - * IDL file
 - * Auto-generated stubs for client, server
 - * Marshalling and unmarshalling of arguments...

12/2/10



Linux buffer cache

- *Buffer cache: just an area of memory
 - * cat /proc/meminfo
- *Caches disk blocks and buffers writes
 - * File read () checks for block already in buffer cache
 - * If not, brings block from disk into memory
 - * File write () is performed in memory first
 - * Data later written back to disk (when? By who?)

12/2/10 13

Buffer cache interface

- *include/linux/buffer head.h
- **★Read a block: FS uses** sb bread():
 - * Find the corresponding buffer_head
 - * Create it if it doesn't exist
 - * Make sure buffer_head->b_data is in memory (read from disk if necessary)

12/2/10 15

Linux buffer cache

- *Block is represented by a buffer head
 - *Actual data is in buffer head->b data
 - * Cache manipulates buffer_head and its b data separately

12/2/10

Buffer cache interface

- *Write a block: mark_buffer_dirty(), then brelse()
 - $oldsymbol{st}$ Mark buffer as changed and release to kernel
 - * Kernel writes block back to disk at a convenient time
 - * bdflush / pdflush threads
 - f x sync command

12/2/10

cse451fs functions

cse451_bread(struct buffer head **pbh,
 struct inode *inode, int_block, int create)

- * Gets buffer_head for given disk block, ensuring its b data is in memory and ready to use
- * Calls cse451 getblk()

cse451_getblk(struct buffer head **pbh, struct inode *inode, int block, int create)

- * Gets buffer_head for given disk block, creating it if it doesn't exist
- * Doesn't necessarily bring b data into cache
- * Both of these functions increment the block's refcount, so must be paired with a brelse()

12/2/10 17

Project 3


*Questions?

12/2/10 18

Networking design principles

- **★**A few key principles:
 - * Layering
 - * End-to-end principle
 - **★** Separation of mechanism and policy
- *All of these apply to operating systems (and elsewhere!) as well

12/2/10



Layering

- *Internet designers didn't get it all right the first time
- **★** Design for choice
 - **★** Rigid designs will be broken

12/2/10

21

Mechanism vs. policy

- *Principle: design system so that mechanisms are separate from policy
 - ★ Implement mechanisms that enable wide range of policies
 - * Caveat: usability ("burden of choice")

12/2/10

23

End-to-end principle

*Danger of putting functionality at lower layers: upper layers won't need it, but will pay cost anyway

* Example: reliability checksums

- *E2E principle says to move functionality towards upper layers (closer to application)
- **★**Other ways of phrasing it:
 - * Smart endpoints, dumb network
 - * Application knows best what it needs

12/2/10 22

12/2/10 2