## **Announcements**

- Questions on the project?
- · New turn-in info online
- · Demos this Friday, 12-1:30

## Motion Estimation

http://www.sandlotscience.com/Distortions/Breathing objects.htm

http://www.sandlotscience.com/Ambiguous/barberpole.htm

#### Today's Readings

- Watt, 10.3-10.4 (handout)
- Trucco & Verri, 8.3 8.4 (skip 8.3.3, read only top half of p. 199) (handout)

## Why estimate motion?

#### Lots of uses

- · Track object behavior
- · Correct for camera jitter (stabilization)
- · Align images (mosaics)
- · 3D shape reconstruction
- · Special effects



## Optical flow







## Problem definition: optical flow



) I(x,

## How to estimate pixel motion from image H to image I?


- Solve pixel correspondence problem
  - given a pixel in H, look for nearby pixels of the same color in I

#### Key assumptions

- · color constancy: a point in H looks the same in I
  - For grayscale images, this is **brightness constancy**
- small motion: points do not move very far

This is called the **optical flow** problem

## Optical flow constraints (grayscale images)



## Let's look at these constraints more closely

· brightness constancy:

$$H(x,y) = I(x+u, y+v)$$

- small motion: (u and v are less than 1 pixel)
  - suppose we take the Taylor series expansion of I:

$$\begin{split} I(x+u,y+v) &= I(x,y) + \frac{\partial I}{\partial x} u + \frac{\partial I}{\partial y} v + \text{higher order terms} \\ &\approx I(x,y) + \frac{\partial I}{\partial x} u + \frac{\partial I}{\partial y} v \end{split}$$

## Optical flow equation

## Combining these two equations

shorthand:  $I_x = \frac{\partial I}{\partial x}$ 0 = I(x + u, y + v) - H(x, y)

$$\approx I(x,y) + I_x u + I_y v - H(x,y)$$

$$\approx (I(x,y) - H(x,y)) + I_x u + I_y v$$

$$\approx I_t + I_x u + I_y v$$

$$\approx I_t + \nabla I \cdot [u \ v]$$

In the limit as u and v go to zero, this becomes exact

$$0 = I_t + \nabla I \cdot \left[ \frac{\partial x}{\partial t} \, \frac{\partial y}{\partial t} \right]$$

## Optical flow equation

$$0 = I_t + \nabla I \cdot [u \ v]$$

Q: how many unknowns and equations per pixel?

· A: u and v are unknown, 1 equation


Intuitively, what does this constraint mean?

- · The component of the flow in the gradient direction is determined
- The component of the flow parallel to an edge is unknown


This explains the Barber Pole illusion

http://www.sandlotscience.com/Ambiguous/barberpole.htm

## Aperture problem



## Aperture problem



## Solving the aperture problem

How to get more equations for a pixel?

- · Basic idea: impose additional constraints
  - most common is to assume that the flow field is smooth locally
  - one method: pretend the pixel's neighbors have the same (u,v)
     » If we use a 5x5 window, that gives us 25 equations per pixel!

$$0 = I_t(\mathbf{p_i}) + \nabla I(\mathbf{p_i}) \cdot [u \ v]$$

$$\begin{bmatrix} I_{X}(\mathbf{p}_{1}) & I_{Y}(\mathbf{p}_{1}) \\ I_{X}(\mathbf{p}_{2}) & I_{Y}(\mathbf{p}_{2}) \\ \vdots \\ I_{X}(\mathbf{p}_{25}) & I_{Y}(\mathbf{p}_{25}) \end{bmatrix} \begin{bmatrix} u \\ v \end{bmatrix} = - \begin{bmatrix} I_{t}(\mathbf{p}_{1}) \\ I_{t}(\mathbf{p}_{2}) \\ \vdots \\ I_{t}(\mathbf{p}_{25}) \end{bmatrix}$$

$$A \qquad d \qquad b$$

$$25x2 \qquad 2x1 \qquad 2bx1$$

## Lukas-Kanade flow

Prob: we have more equations than unknowns

$$A \atop 25x2} d = b \atop 25x1} \longrightarrow \text{ minimize } ||Ad - b||^2$$

Solution: solve least squares problem

minimum least squares solution given by solution (in d) of:

$$(A^T A) \underset{2 \times 2}{d} = A^T b$$

$$\begin{bmatrix} \sum I_x I_x & \sum I_x I_y \\ \sum I_x I_y & \sum I_y I_y \end{bmatrix} \begin{bmatrix} u \\ v \end{bmatrix} = - \begin{bmatrix} \sum I_x I_t \\ \sum I_y I_t \end{bmatrix}$$

$$A^T A \qquad A^T b$$

- The summations are over all pixels in the K x K window
- This technique was first proposed by Lukas & Kanade (1981)
  - described in Trucco & Verri handout

## Conditions for solvability

Optimal (u, v) satisfies Lucas-Kanade equation

$$\begin{bmatrix} \sum I_x I_x & \sum I_x I_y \\ \sum I_x I_y & \sum I_y I_y \end{bmatrix} \begin{bmatrix} u \\ v \end{bmatrix} = - \begin{bmatrix} \sum I_x I_t \\ \sum I_y I_t \end{bmatrix}$$

$$A^T A \qquad A^T b$$

#### When is This Solvable?

- A<sup>T</sup>A should be invertible
- A<sup>T</sup>A should not be too small due to noise
- eigenvalues  $\lambda_1$  and  $\lambda_2$  of  $\mathbf{A}^T\mathbf{A}$  should not be too small
- A<sup>T</sup>A should be well-conditioned
  - $\lambda_1/$   $\lambda_2$  should not be too large ( $\lambda_1$  = larger eigenvalue)

## Eigenvectors of ATA

$$A^TA = \left[ \begin{array}{cc} \sum I_x I_x & \sum I_x I_y \\ \sum I_x I_y & \sum I_y I_y \end{array} \right] = \sum \left[ \begin{array}{c} I_x \\ I_y \end{array} \right] [I_x \ I_y] = \sum \nabla I (\nabla I)^T$$

## Suppose (x,y) is on an edge. What is $A^TA$ ? derive on board

- · gradients along edge all point the same direction
- gradients away from edge have small magnitude


$$\left(\sum \nabla I(\nabla I)^{T}\right) \approx k \nabla I \nabla I^{T}$$
$$\left(\sum \nabla I(\nabla I)^{T}\right) \nabla I = k \|\nabla I\| \nabla I$$


- $\nabla I$  is an eigenvector with eigenvalue  $|k||\nabla I||$
- What's the other eigenvector of A<sup>T</sup>A?
  - let N be perpendicular to  $\nabla I$


$$\left(\sum \nabla I(\nabla I)^T\right)N = 0$$

- N is the second eigenvector with eigenvalue 0

The eigenvectors of A<sup>T</sup>A relate to edge direction and magnitude







# This is a two image problem BUT Can measure sensitivity by just looking at one of the imagesl This tells us which pixels are easy to track, which are hard very useful later on when we do feature tracking...

Observation

#### Errors in Lukas-Kanade

What are the potential causes of errors in this procedure?

- Suppose  $A^TA$  is easily invertible
- · Suppose there is not much noise in the image

#### When our assumptions are violated

- · Brightness constancy is **not** satisfied
- · The motion is not small
- · A point does not move like its neighbors
  - window size is too large
  - what is the ideal window size?

## Improving accuracy

Recall our small motion assumption

$$0 = I(x + u, y + v) - H(x, y)$$
  
 
$$\approx I(x, y) + I_x u + I_y v - H(x, y)$$

#### This is not exact

• To do better, we need to add higher order terms back in:

$$= I(x,y) + I_x u + I_y v + \text{higher order terms} - H(x,y)$$

#### This is a polynomial root finding problem

Can solve using Newton's method

1D case

- Also known as **Newton-Raphson** method
- Today's reading (first four pages)
- » http://www.ulib.org/webRoot/Books/Numerical\_Recipes/bookcpdf/c9-4.pdf
- · Lukas-Kanade method does one iteration of Newton's method
  - Better results are obtained via more iterations

## **Iterative Refinement**

#### Iterative Lukas-Kanade Algorithm

- 1. Estimate velocity at each pixel by solving Lucas-Kanade equations
- 2. Warp H towards I using the estimated flow field - use image warping techniques
- 3. Repeat until convergence

## Revisiting the small motion assumption



Is this motion small enough?

- Probably not—it's much larger than one pixel
- How might we solve this problem?


## Reduce the resolution!












## Coarse-to-fine optical flow estimation run iterative L-K warp & upsample run iterative L-K Gaussian pyramid of image I Gaussian pyramid of image H



## Motion tracking


Suppose we have more than two images

- How to track a point through all of the images?
   In principle, we could estimate motion between each pair of consecutive frames
  - Given point in first frame, follow arrows to trace out it's path
  - - » small errors will tend to grow and grow over time—the point will drift way off course

## Feature Tracking

- · Choose only the points ("features") that are easily tracked
- · How to find these features?
  - windows where  $\sum 
    abla I (
    abla I)^T$  has two large eigenvalues
- · Called the Harris Corner Detector

## **Feature Detection**



## Tracking features

### Feature tracking

- · Compute optical flow for that feature for each consecutive H, I Complications:
  - · Occlusions—feature may disappear
    - need mechanism for deleting, adding new features
  - · Changes in shape, orientation
    - allow the feature to deform
  - · Changes in color
  - · Large motions
    - will pyramid techniques work for feature tracking?

## Handling large motions

L-K requires small motion

If the motion is much more than a pixel, use discrete **search** instead





- · Given window W in H, find best matching window in I
- · Minimize sum squared difference (SSD) of pixels in window

$$min_{(u,v)} \left\{ \sum_{(x,y) \in W} |I(x+u,y+v) - H(x,y)|^2 \right\}$$

• Solve by doing a search over a specified range of (u,v) values - this (u,v) range defines the **search window** 

## **Tracking Over Many Frames**

#### Feature tracking with m frames

- 1. Select features in first frame
- 2. Given feature in frame i, compute position in i+1
- 3. Select more features if needed
- 4. i = i + 1
- 5. If i < m, go to step 2

#### Issues

- · Discrete search vs. Lucas Kanade?
  - depends on expected magnitude of motion
  - discrete search is more flexible
- How often to update feature template?
- update often enough to compensate for distortion
- updating too often causes drift
- · How big should search window be?
  - too small: lost features. Too large: slow

## Incorporating Dynamics

- Can get better performance if we know something about the way points move
- · Most approaches assume constant velocity

$$\dot{\mathbf{x}}_{i+1} = \dot{\mathbf{x}}_i$$

$$\mathbf{x}_{i+1} = 2\mathbf{x}_i - \mathbf{x}_{i-1}$$

or constant acceleration

$$\ddot{\mathbf{x}}_{i+1} \ = \ \ddot{\mathbf{x}}_i$$

$$\mathbf{x}_{i+1} = 3\mathbf{x}_i - 3\mathbf{x}_{i-1} + \mathbf{x}_{i-2}$$

· Use above to predict position in next frame, initialize search

## Feature tracking demo


#### Oxford video

http://www.toulouse.ca/?/CamTracker/?/CamTracker/FeatureTracking.html

## MPEG—application of feature tracking

• http://www.pixeltools.com/pixweb2.html

## Image alignment



Goal: estimate single (u,v) translation for entire image

• Easier subcase: solvable by pyramid-based Lukas-Kanade

## Summary

Things to take away from this lecture

- Optical flow problem definition
- Aperture problem and how it arises
- Assumptions
- Brightness constancy, small motion, smoothness
- · Derivation of optical flow constraint equation
- · Lukas-Kanade equation
- Derivation
   Conditions for solvability
   meanings of eigenvalues and eigenvectors
- · Iterative refinement - Newton's method
- Coarse-to-fine flow estimation Feature tracking
  - Harris feature detector
  - L-K vs. discrete search method
     Tracking over many frames
  - Prediction using dynamics
- Applications
  - MPEG video compression