

CSE-505: Programming Languages

Lecture 17 — Recursive Types

Zach Tatlock
2015

Where are we

- ▶ System F gave us type abstraction
 - ▶ code reuse
 - ▶ strong abstractions
 - ▶ different from real languages (like ML), but the right foundation
- ▶ This lecture: Recursive Types (different use of type variables)
 - ▶ For building unbounded data structures
 - ▶ Turing-completeness without a fix primitive
- ▶ Future lecture (?): Existential types (dual to universal types)
 - ▶ First-class abstract types
 - ▶ Closely related to closures and objects
- ▶ Future lecture (?): Type-and-effect systems

Recursive Types

We could add list types ($\text{list}(\tau)$) and primitives ($[]$, $::$, match), but we want user-defined recursive types

Intuition:

```
type intlist = Empty | Cons int * intlist
```

Which is roughly:

```
type intlist = unit + (int * intlist)
```

- ▶ Seems like a named type is unavoidable
 - ▶ But that's what we thought with `let rec` and we used `fix`
- ▶ Analogously to **fix** $\lambda x. e$, we'll introduce $\mu\alpha.\tau$
 - ▶ Each α “stands for” entire $\mu\alpha.\tau$

Mighty μ

In τ , type variable α stands for $\mu\alpha.\tau$, bound by μ

Examples (of many possible encodings):

- ▶ int list (finite or infinite): $\mu\alpha.\mathbf{unit} + (\mathbf{int} * \alpha)$
- ▶ int list (infinite “stream”): $\mu\alpha.\mathbf{int} * \alpha$
 - ▶ Need laziness (thunking) or mutation to build such a thing
 - ▶ Under CBV, can build values of type $\mu\alpha.\mathbf{unit} \rightarrow (\mathbf{int} * \alpha)$
- ▶ int list list: $\mu\alpha.\mathbf{unit} + ((\mu\beta.\mathbf{unit} + (\mathbf{int} * \beta)) * \alpha)$

Examples where type variables appear multiple times:

- ▶ int tree (data at nodes): $\mu\alpha.\mathbf{unit} + (\mathbf{int} * \alpha * \alpha)$
- ▶ int tree (data at leaves): $\mu\alpha.\mathbf{int} + (\alpha * \alpha)$

Using μ types

How do we build and use int lists ($\mu\alpha.\mathbf{unit} + (\mathbf{int} * \alpha)$)?

We would like:

Using μ types

How do we build and use int lists ($\mu\alpha.\mathbf{unit} + (\mathbf{int} * \alpha)$)?

We would like:

▶ empty list = $\mathbf{A}()$

Has type: $\mu\alpha.\mathbf{unit} + (\mathbf{int} * \alpha)$

Using μ types

How do we build and use int lists $(\mu\alpha.\mathbf{unit} + (\mathbf{int} * \alpha))$?

We would like:

▶ empty list = $\mathbf{A}()$

Has type: $\mu\alpha.\mathbf{unit} + (\mathbf{int} * \alpha)$

▶ cons = $\lambda x:\mathbf{int}.\lambda y:(\mu\alpha.\mathbf{unit} + (\mathbf{int} * \alpha)).\mathbf{B}((x, y))$

Has type:

$\mathbf{int} \rightarrow (\mu\alpha.\mathbf{unit} + (\mathbf{int} * \alpha)) \rightarrow (\mu\alpha.\mathbf{unit} + (\mathbf{int} * \alpha))$

Using μ types

How do we build and use int lists $(\mu\alpha.\mathbf{unit} + (\mathbf{int} * \alpha))$?

We would like:

- ▶ empty list = $\mathbf{A}()$
Has type: $\mu\alpha.\mathbf{unit} + (\mathbf{int} * \alpha)$
- ▶ cons = $\lambda x:\mathbf{int}.\lambda y:(\mu\alpha.\mathbf{unit} + (\mathbf{int} * \alpha)).\mathbf{B}((x, y))$
Has type:
 $\mathbf{int} \rightarrow (\mu\alpha.\mathbf{unit} + (\mathbf{int} * \alpha)) \rightarrow (\mu\alpha.\mathbf{unit} + (\mathbf{int} * \alpha))$
- ▶ head =
 $\lambda x:(\mu\alpha.\mathbf{unit} + (\mathbf{int} * \alpha)).\mathbf{match} x \mathbf{with} \mathbf{A}_.\mathbf{A}() \mid \mathbf{B}y.\mathbf{B}(y.1)$
Has type: $(\mu\alpha.\mathbf{unit} + (\mathbf{int} * \alpha)) \rightarrow (\mathbf{unit} + \mathbf{int})$

Using μ types

How do we build and use int lists ($\mu\alpha.\mathbf{unit} + (\mathbf{int} * \alpha)$)?

We would like:

- ▶ empty list = $\mathbf{A}()$
Has type: $\mu\alpha.\mathbf{unit} + (\mathbf{int} * \alpha)$
- ▶ cons = $\lambda x:\mathbf{int}.\lambda y:(\mu\alpha.\mathbf{unit} + (\mathbf{int} * \alpha)).\mathbf{B}((x, y))$
Has type:
 $\mathbf{int} \rightarrow (\mu\alpha.\mathbf{unit} + (\mathbf{int} * \alpha)) \rightarrow (\mu\alpha.\mathbf{unit} + (\mathbf{int} * \alpha))$
- ▶ head =
 $\lambda x:(\mu\alpha.\mathbf{unit} + (\mathbf{int} * \alpha)).\mathbf{match } x \mathbf{ with } \mathbf{A}_.\mathbf{A}() \mid \mathbf{B}y.\mathbf{B}(y.1)$
Has type: $(\mu\alpha.\mathbf{unit} + (\mathbf{int} * \alpha)) \rightarrow (\mathbf{unit} + \mathbf{int})$
- ▶ tail =
 $\lambda x:(\mu\alpha.\mathbf{unit} + (\mathbf{int} * \alpha)).\mathbf{match } x \mathbf{ with } \mathbf{A}_.\mathbf{A}() \mid \mathbf{B}y.\mathbf{B}(y.2)$
Has type:
 $(\mu\alpha.\mathbf{unit} + (\mathbf{int} * \alpha)) \rightarrow (\mathbf{unit} + \mu\alpha.\mathbf{unit} + (\mathbf{int} * \alpha))$

Using μ types

How do we build and use int lists ($\mu\alpha.\mathbf{unit} + (\mathbf{int} * \alpha)$)?

We would like:

- ▶ empty list = $\mathbf{A}()$
Has type: $\mu\alpha.\mathbf{unit} + (\mathbf{int} * \alpha)$
- ▶ cons = $\lambda x:\mathbf{int}.\lambda y:(\mu\alpha.\mathbf{unit} + (\mathbf{int} * \alpha)).\mathbf{B}((x, y))$
Has type:
 $\mathbf{int} \rightarrow (\mu\alpha.\mathbf{unit} + (\mathbf{int} * \alpha)) \rightarrow (\mu\alpha.\mathbf{unit} + (\mathbf{int} * \alpha))$
- ▶ head =
 $\lambda x:(\mu\alpha.\mathbf{unit} + (\mathbf{int} * \alpha)).\mathbf{match} x \mathbf{with} \mathbf{A}_.\mathbf{A}() \mid \mathbf{B}y.\mathbf{B}(y.1)$
Has type: $(\mu\alpha.\mathbf{unit} + (\mathbf{int} * \alpha)) \rightarrow (\mathbf{unit} + \mathbf{int})$
- ▶ tail =
 $\lambda x:(\mu\alpha.\mathbf{unit} + (\mathbf{int} * \alpha)).\mathbf{match} x \mathbf{with} \mathbf{A}_.\mathbf{A}() \mid \mathbf{B}y.\mathbf{B}(y.2)$
Has type:
 $(\mu\alpha.\mathbf{unit} + (\mathbf{int} * \alpha)) \rightarrow (\mathbf{unit} + \mu\alpha.\mathbf{unit} + (\mathbf{int} * \alpha))$

But our typing rules allow none of this (yet)

Using μ types (continued)

For empty list = $\mathbf{A}()$, one typing rule applies:

$$\frac{\Delta; \Gamma \vdash e : \tau_1 \quad \Delta \vdash \tau_2}{\Delta; \Gamma \vdash \mathbf{A}(e) : \tau_1 + \tau_2}$$

So we could show

$$\Delta; \Gamma \vdash \mathbf{A}() : \mathbf{unit} + (\mathbf{int} * (\mu\alpha.\mathbf{unit} + (\mathbf{int} * \alpha)))$$

(since $FTV(\mathbf{int} * \mu\alpha.\mathbf{unit} + (\mathbf{int} * \alpha)) = \emptyset \subseteq \Delta$)

Using μ types (continued)

For empty list = $\mathbf{A}()$, one typing rule applies:

$$\frac{\Delta; \Gamma \vdash e : \tau_1 \quad \Delta \vdash \tau_2}{\Delta; \Gamma \vdash \mathbf{A}(e) : \tau_1 + \tau_2}$$

So we could show

$$\Delta; \Gamma \vdash \mathbf{A}() : \mathbf{unit} + (\mathbf{int} * (\mu\alpha.\mathbf{unit} + (\mathbf{int} * \alpha)))$$

(since $FTV(\mathbf{int} * \mu\alpha.\mathbf{unit} + (\mathbf{int} * \alpha)) = \emptyset \subseteq \Delta$)

But we want $\mu\alpha.\mathbf{unit} + (\mathbf{int} * \alpha)$

Using μ types (continued)

For empty list = $\mathbf{A}(())$, one typing rule applies:

$$\frac{\Delta; \Gamma \vdash e : \tau_1 \quad \Delta \vdash \tau_2}{\Delta; \Gamma \vdash \mathbf{A}(e) : \tau_1 + \tau_2}$$

So we could show

$$\Delta; \Gamma \vdash \mathbf{A}() : \mathbf{unit} + (\mathbf{int} * (\mu\alpha.\mathbf{unit} + (\mathbf{int} * \alpha)))$$

(since $FTV(\mathbf{int} * \mu\alpha.\mathbf{unit} + (\mathbf{int} * \alpha)) = \emptyset \subseteq \Delta$)

But we want $\mu\alpha.\mathbf{unit} + (\mathbf{int} * \alpha)$

Notice: $\mathbf{unit} + (\mathbf{int} * (\mu\alpha.\mathbf{unit} + (\mathbf{int} * \alpha)))$ is
 $(\mathbf{unit} + (\mathbf{int} * \alpha))[(\mu\alpha.\mathbf{unit} + (\mathbf{int} * \alpha))/\alpha]$

Using μ types (continued)

For empty list = $\mathbf{A}()$, one typing rule applies:

$$\frac{\Delta; \Gamma \vdash e : \tau_1 \quad \Delta \vdash \tau_2}{\Delta; \Gamma \vdash \mathbf{A}(e) : \tau_1 + \tau_2}$$

So we could show

$$\Delta; \Gamma \vdash \mathbf{A}() : \mathbf{unit} + (\mathbf{int} * (\mu\alpha.\mathbf{unit} + (\mathbf{int} * \alpha)))$$

(since $FTV(\mathbf{int} * \mu\alpha.\mathbf{unit} + (\mathbf{int} * \alpha)) = \emptyset \subseteq \Delta$)

But we want $\mu\alpha.\mathbf{unit} + (\mathbf{int} * \alpha)$

Notice: $\mathbf{unit} + (\mathbf{int} * (\mu\alpha.\mathbf{unit} + (\mathbf{int} * \alpha)))$ is
 $(\mathbf{unit} + (\mathbf{int} * \alpha))[(\mu\alpha.\mathbf{unit} + (\mathbf{int} * \alpha))/\alpha]$

The key: Subsumption — recursive types are equal to their “unrolling”

Return of subtyping

Can use *subsumption* and these subtyping rules:

ROLL

$$\frac{}{\tau[(\mu\alpha.\tau)/\alpha] \leq \mu\alpha.\tau}$$

UNROLL

$$\frac{}{\mu\alpha.\tau \leq \tau[(\mu\alpha.\tau)/\alpha]}$$

Subtyping can “roll” or “unroll” a recursive type

Can now give empty-list, cons, and head the types we want:
Constructors use roll, destructors use unroll

Notice how little we did: One new form of type $(\mu\alpha.\tau)$ and two new subtyping rules

(Skipping: Depth subtyping on recursive types is very interesting)

Metatheory

Despite additions being minimal, must reconsider how recursive types change STLC and System F:

- ▶ Erasure (no run-time effect): unchanged
- ▶ Termination: changed!
 - ▶ $(\lambda x:\mu\alpha.\alpha \rightarrow \alpha. x x)(\lambda x:\mu\alpha.\alpha \rightarrow \alpha. x x)$
 - ▶ In fact, we're now Turing-complete without fix (actually, can type-check every closed λ term)
- ▶ Safety: still safe, but Canonical Forms harder
- ▶ Inference: Shockingly efficient for "STLC plus μ "
(A great contribution of PL theory with applications in OO and XML-processing languages)

Syntax-directed μ types

Recursive types via subsumption “seems magical”

Instead, we can make programmers tell the type-checker where/how to roll and unroll

“Iso-recursive” types: remove subtyping and add expressions:

$$\begin{aligned}\tau & ::= \dots \mid \mu\alpha.\tau \\ e & ::= \dots \mid \mathbf{roll}_{\mu\alpha.\tau} e \mid \mathbf{unroll} e \\ v & ::= \dots \mid \mathbf{roll}_{\mu\alpha.\tau} v\end{aligned}$$

$$\frac{e \rightarrow e'}{\mathbf{roll}_{\mu\alpha.\tau} e \rightarrow \mathbf{roll}_{\mu\alpha.\tau} e'}$$

$$\frac{e \rightarrow e'}{\mathbf{unroll} e \rightarrow \mathbf{unroll} e'}$$

$$\frac{}{\mathbf{unroll} (\mathbf{roll}_{\mu\alpha.\tau} v) \rightarrow v}$$

$$\frac{\Delta; \Gamma \vdash e : \tau[(\mu\alpha.\tau)/\alpha]}{\Delta; \Gamma \vdash \mathbf{roll}_{\mu\alpha.\tau} e : \mu\alpha.\tau}$$

$$\frac{\Delta; \Gamma \vdash e : \mu\alpha.\tau}{\Delta; \Gamma \vdash \mathbf{unroll} e : \tau[(\mu\alpha.\tau)/\alpha]}$$

Syntax-directed, continued

Type-checking is syntax-directed / No subtyping necessary

Canonical Forms, Preservation, and Progress are simpler

This is an example of a key trade-off in language design:

- ▶ Implicit typing can be impossible, difficult, or confusing
- ▶ Explicit coercions can be annoying and clutter language with no-ops
- ▶ Most languages do some of each

Anything is decidable if you make the code producer give the implementation enough “hints” about the “proof”

ML datatypes revealed

How is $\mu\alpha.\tau$ related to

type $t = \text{Foo of int} \mid \text{Bar of int} * t$

Constructor use is a “sum-injection” followed by an *implicit roll*

- ▶ So $\text{Foo } e$ is really **roll_t Foo(e)**
- ▶ That is, $\text{Foo } e$ has type t (the rolled type)

A pattern-match has an *implicit unroll*

- ▶ So $\text{match } e \text{ with} \dots$ is really $\text{match unroll } e \text{ with} \dots$

This “trick” works because different recursive types use different tags – so the type-checker knows *which* type to roll to