

Smartphone Mobile Computing

CSEP590B/F Winter 2011 (first offering)

4th Lecture, 31 January 2011

Instructor:

Gaetano Borriello

Teaching Assistants:

Temitope Oluwafemi and Cary Anderson

Overview for Today


- **Finish up on sensing from last week**
- **ML applied to sensor data for determining user context**
- **Q/A on sensing**

- **Group projects: questions on mid-term project report**

- **Communication methods**
- **Smartphone and SMS, Bluetooth, WiFi, GPRS**
- **Future directions**

Wireless Communication

- **Serial communication**
- **Allocated a frequency of operation**
 - Could be a range of frequencies
 - Regulated by FCC (Federal Communications Commission) in US
 - Unfortunately, allocations are not world-wide



Electromagnetic Spectrum (3kHz – 300GHz)

UNITED STATES FREQUENCY ALLOCATIONS THE RADIO SPECTRUM

RADIO SERVICES COLOR LEGEND

- | | | | |
|--|--|--|--|
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |


ACTIVITY CODE

- GOVERNMENT EXCLUSIVE
- GOVERNMENT/GOVERNMENT SHARED
- NON-GOVERNMENT EXCLUSIVE

ALLOCATION USAGE DESIGNATION

Service	Primary	Secondary	Co-Channel	Other
Primary	P			
Secondary		S		
Co-Channel			C	
Other				O

This chart is made available in the interest of the public and is not intended to be used for legal purposes. It is provided as a reference only and is not intended to be used for legal purposes. It is provided as a reference only and is not intended to be used for legal purposes.



How wireless frequencies are allocated

- Garage door openers, alarm systems, etc. – 40MHz
- Cordless phones: 40-50MHz, 900MHz, 2.4GHz, 5.8GHz
- Baby monitors: 49MHz
- Radio controlled toys: 27-75MHz
- Wildlife tracking collars: 215-220MHz
- MIR space station: 145-437MHz
- Cell phones: 824-849MHz, 869-894MHz, 1850-1990MHz (850/1900 in US, 900/1800 in EU)
- Public safety (fire, police, ambulance): 849-869MHz
- Air traffic control radar: 960MHz-1.215GHz
- Global Positioning System: 1.227-1.575MHz
- Satellite radio: 2.3GHz
- WiFi/802.11b/g and Bluetooth: 2.4GHz
- Zigbee/802.15.4: 868MHz, 915MHz, 2.4GHz
- Microwave ovens: 2.4Ghz
- TV: 54-216 (VHF 2-13), 470-806MHz (UHF 14-69)
- Ultra-wide-band: 3.1-10.6GHz
- ISM (industrial, scientific, medical): 900MHz, 1.8GHz, 2.4GHz, 5.8GHz

Considerations in choosing a frequency





- **Carrier frequency**
 - Signal that is modulated to carry data
 - Frequency is not equal to bandwidth
- **Ability to carry data (modulation rate)**
- **Availability of devices to transmit and receive signals**
- **Interference from other devices in same band**
 - ISM bands limit power output
- **Interactions of radiation with environment**
 - absorption by water, metal, building materials, foliage
- **Reflection and multi-path properties**
 - constructive/destructive interference patterns (e.g., nulls)

Radio Protocols for Wireless Networks

- **Cellular (850-2100MHz)**
 - Voice, SMS, MMS, GPRS
- **WiFi (2.4GHz, 5GHz)**
 - Wireless LAN
- **Bluetooth (2.4GHz)**
 - Common in many consumer devices (headsets, cars, phones, etc.)
- **Zigbee (850-930MHz)**
 - Next generation radio for sensor networks and consumer devices

Communication methods

■ Modulation

Modulation Technique	Waveform
No encoding (Baseband)	
On-Off Keying (OOK)	
Frequency Shift Keying (FSK)	
Binary Phase Shift Keying (BPSK)	
Complementary Code Keying (CCK)	

■ Multiplexing

- TDMA – time division - take turns talking
- FDMA – frequency division - talk at different pitches
- CDMA – code division - use different languages

Short Messaging Service (SMS)

- **First “data” service for mobile phones**
- **Allows users to exchange brief text strings**
- **Addressing uses standard phone numbers**
 - easy setup, supported by all tiers of phones, no separate accounts
- **160 characters: 1120 bits at 7bits/character**
 - extensions for unicode halve this number
 - concatenated SMS for longer data
- **6 trillion SMS sent in 2010 – 35% in US and Philippines**
- **Cost is relatively high – more than data from Hubble telescope**
 - 0.20USD/message leads to 1500USD per MB (US carriers)
 - 0.01USD/message is still 75USD per MB (India)
 - India: 3USD for 15000 SMS, US: 20USD for unlimited
 - incoming vs. outgoing message charges

SMS history

- **Uses the control system of the GSM standard**
- **In 1993, Nokia realized they could sell unused bandwidth for an instant messaging service**
- **USSD is the still free variant of SMS**
 - carriers allocate USSD short codes for subsidized service
- **Input formats – focus on standard 12-key keyboard**
 - multi-tap is most popular (tap 3 times for “v” on 8-tuv)
 - T9 gained momentum until full-keyboard phones (predictive text)
 - auto-completion
- **Output formats**
 - single message queue
 - “conversations”

SMS services

■ Short codes

- easier to remember shorter “phone numbers” for popular services


■ Payment

- transfer of payments associated with certain numbers (per msg)

■ Internet gateways

- allow arbitrary services
- grab data from web and package it into SMS (e.g., OneBusAway)
- require appropriate message formats (usability issue)

SMS growth over last 3 years



Group text, Twitter



GeoChat

InSTEDD GeoChat 1.0 Disaster-ready Group Communications

Use SMS text messaging to coordinate with your team on the surface of a map!



Keep government agencies, first responders, and the local community in sync

*Broadcast alerts, form teams, and **swarm** around critical events as they unfold*



Multi-media Messaging Service (MMS)

- **Similar to SMS, but no size limit**
 - began in 2002
 - really only practical on 3G networks (but works with some 2G as well)
 - 50 billion messages per year generating USD26B (2008)
 - Scandinavia is most advanced market
- **Mostly used by feature phones with cameras**
 - attach multi-media files to text message
 - if receiver isn't capable, then collected at web site, SMS with link sent
- **Pricing similar to SMS – by the message**
 - much cheaper by the bit
 - major issues are in encoding of data (currently, MIME-types) and codecs
 - no bulk messaging

MMS interface



New MMS(27K,1/1)



To:

Subject:



Insert Text...



Insert Audio...


Send

Menu



MMS services expand connection to web

- Keyword to image-based search (possibly tied to location)
- Navigation instructions for non-smartphones
- Automatic translation services (e.g., Google Goggles)



Smartphones and SMS/MMS


- Legacy support for migration from feature phones
- Interplay with direct Internet access over GPRS
- Services/apps governed by
 - pricing structure
 - familiar usage models and interfaces
- Provide richer text entry and more media types
 - Swype
 - video




Bluetooth

■ Short-range radio at 2.4GHz

- Available globally for unlicensed users
- Low-power
- Low-cost
- Cable replacement
- Devices within 10m can share up to 1Mb/sec – 700Kb/sec effective
- Universal short-range wireless capability



Harald Blatand II
unified Norway
and Denmark
in 10th century



Bluetooth application areas

■ Data and voice access points

- Real-time voice and data transmissions
- Cordless headsets
- Three-in-one phones: cell, cordless, walkie-talkie

■ Cable replacement

- Eliminates need for numerous cable attachments for connection
- Automatic synchronization when devices within range

■ Ad hoc networking

- Can establish connections between devices in range
- Devices can “imprint” on each other so that authentication is not required for each instance of communication
- Support for object exchange (files, calendar entries, business cards)


Protocol architecture

■ Bluetooth is a layered protocol architecture

- Core protocols
- Cable replacement and telephony control protocols
- Specialized protocols (profiles)

■ Core protocols

- Radio and baseband
- Link manager protocol (LMP)
- Logical link control and adaptation protocol (L2CAP)
- Service discovery protocol (SDP)



Protocol architecture

- **Cable replacement protocol**
 - RFCOMM
- **Telephony control protocol**
 - Telephony control specification – binary (TCS BIN)
- **Adopted protocols**
 - TCP/UDP/IP
 - OBEX
 - WAP
- **Profiles – vertical slide through the protocol stack**
 - Basis of interoperability
 - Each device supports at least one profile
 - Defined based on usage models
 - e.g., headset and phone, camera and TV, mp3player and car, etc.


Piconets and scatternets

■ Piconet

- Basic unit of Bluetooth networking
- Master and up to 7 slave devices
- Master determines channel and phase


■ Scatternet

- Device in one piconet may exist as master or slave in another piconet
- Allows many devices to share same area
- Makes efficient use of bandwidth



Frequency hopping

- Provides resistance to interference and multipath effects
- Total bandwidth divided into 1MHz physical channels
- Frequency hopping occurs by moving transmitter/receiver from one channel to another in a pseudo-random sequence
- Hopping sequence shared with all devices in the same piconet so that they can hop together and stay in communication



Links between master and slave

■ Synchronous connection-oriented (SCO)

- Allocates fixed bandwidth between point-to-point connection of master and slave
- Master maintains link using reserved slots
- Master can support three simultaneous links


■ Asynchronous connection-less (ACL)

- Point-to-multipoint link between master and all slaves
- Only single ACL link can exist

Pairing

- **Linking two devices via a shared PIN (old method)**
- **One device provides a pass-key to be entered on the other**
 - limited by I/O on some devices (e.g., head set)
- **Once paired, devices can re-discover each other and connect automatically**
- **De-pairing?**

Bluetooth packet format



Scenario steps

- **Master device (e.g., PDA) pages for nearby devices**
- **Receives response from 0, 1, or more devices**
 - Slave device (e.g., headphone) responds to page
- **Determines which it “knows” – established connections**
- **L2CAP establishes Bluetooth connection assigning paging device to be master**
- **Devices exchange profiles they both support**
- **Agree upon profile (e.g., audio streaming)**
- **Master sends audio data**
 - Two devices synchronize their frequency hopping
- **Keep-alive packets used to maintain connections**
- **Connections dropped if keep-alive packets are not ack’ed**

Limitations/Issues

- **Discovery time on the order of 10sec for unknown devices**
- **Interaction with user required to connect to unknown devices or if multiple masters**
- **Can connect 8 devices at a time, more need to be multiplexed radically lowering throughput**
- **Doesn't support simple broadcast – need to be on same frequency hopping schedule**
- **Effective bandwidth closer to 500Kbps (within one scatternet, order of magnitude lower if between two)**

WiFi

■ Infrastructure-based

- most popular
- access points (APs) act as wireless-to-wired Ethernet gateways

■ Ad hoc network

- not very popular – so far




Figure 4-23. 802.11 architecture. (a) Infrastructure mode. (b) Ad-hoc mode.


Types of WiFi (IEEE 802.11)

- **802.11b – spread spectrum – 1999**
 - 11 Mbps but also supports 5.5, 2, and 1 (2.4GHz)
- **802.11a – orthogonal frequency division multiplexing (OFDM)**
 - 54 Mbps (5GHz)
- **802.11g – OFDM with 802.11b compatibility – 2003**
 - 6 to 54 Mbps (2.4 GHz) – shorter range than 802.11b
- **802.11n – multiple antenna OFDM (MIMO/OFDM) – 2009**
 - 100 – 600 Mbps (2.4 GHz but wider band)

- **Most common today is b/g combination**


Major issues with WiFi

- **Can't transmit and receive simultaneously**
 - outgoing signal swamps any incoming signals
- **Difficult to detect collisions – DCF (distributed coord. function)**
 - collision at receiver may not be seen by sender
 - collision avoidance instead of collision detection
 - use of acks to determine if collision occurred




Hidden and exposed devices

A wants to send to B
but cannot hear that
B is busy



(a)

B wants to send to C
but mistakenly thinks
the transmission will fail



(b)

Figure 4-26. (a) The hidden terminal problem. (b) The exposed terminal problem.

Access points

- Gateways between wireless and wired networks
- Devices associate with an access point
 - security managed at association with passcode or registration (WPA2)
- Orchestrate their associated clients
 - beacon frames (provide way to fingerprint WiFi environment and used for indoor location)
 - reservations and buffer status
 - fairness among clients




Figure 4-28. Interframe spacing in 802.11.

WiFi packet format




Figure 4-29. Format of the 802.11 data frame.

Hotspot and peer-to-peer

- **WiFi devices can act as hotspots (APs) for others**
 - must allocate IP addresses just like an AP
 - tethering of laptop through smartphone via WiFi to access web
- **Ad hoc networks of peers**
 - must decide on scope of network (temporary SSID)
 - allocate IP addresses to participants (distributed/centralized)

GPRS

- **2G/3G data connection standard - 200 Kbits/sec**
- **High-speed download packet access (HSDPA/3.5G) can go up 14.4Mbps**
- **HSPA+ w/ MIMO at 42Mbps (2010) and can go up to 84Mbps**
- **Similar architecture to infrastructure-based WiFi**
 - cell towers as access points
 - more emphasis on billing and “roaming”

GPRS Attach and PDP Context Activation (GPRS Attach and PDP Context Activation for a Class B Terminal)											
GSM Coverage	GSM GPRS Network										EventHelix.com/EventStudio 2.5
Cell	BSS	Core Network			Old Core Network		GGSN Site			GSM Databases	
UT	BSC	SGSN	DNS Server	MSC VLR	Old SGSN	Old MSC VLR	GGSN	Radius Server	DHCP Server	EIR	HLR


01-Feb-05 07:06 (Page 1)

This sequence diagram was generated with EventStudio 2.5 (<http://www.EventHelix.com/EventStudio>).

We explore the sequence of interactions involved in a GPRS terminal attaching to the network. The combined attach and PDP context activation of a Class B GPRS terminal will be covered here.

Copyright © 2005 EventHelix.com Inc. All Rights Reserved.

GPRS Attach



The terminal initiates the attach procedure after power on. The message contains the previously used TMSI (Temporary Mobile Subscriber Id). The mobile network identity, the location area and routing area information is also included in the message.

The SGSN (Serving GPRS Support Node) searches for TMSI in its database.

No entry is found for the TMSI, so the SGSN uses the old location area information to identify the old SGSN where this terminal was being served.

The old SGSN responds with the GPRS mobile's IMSI (International Mobile Subscriber Identity) to the SGSN.


The SGSN asks the terminal to identify itself.


The terminal responds back.


The SGSN authenticates the GPRS mobile by sending a RAND value (a random value).

The SIM applies secret GSM algorithms on the RAND and the secret key KI to obtain the session key Kc and SRES.

The computed SRES value is passed to the SGSN.







4G

- **WiMax and LTE (steps toward 4G) now at 50Mbps**
- **4G will be 100Mbps (high mobility) to 1Gbps (low mobility)**
 - data is primary target (voice as another type of data)
 - will all use OFDM and MIMO

WiMax

■ Worldwide Interoperability for Microwave Access

- first developed in 2001 as IEEE 802.16
- 10x range of 802.11b at 2.5GHz (licensed spectrum)
- careful control by base station of all traffic
- security built-in from start




Figure 4-33. (a) A generic frame. (b) A bandwidth request frame.

NFC/RFID

- RFID read/write – 100Kbps

